

Order
 Quote

Company name:		
Contact name:		Contact telephone:
Company postcode:	Today's date:	Requested delivery date:
Page: _____ of _____	Your reference:	Our order number:

System/Bead type	Sculptured	
Joint type	Timberweld®	
Colour		
Glazing	Glazed	Unglazed
Glass spec to WER	C	A
Secured by Design	Yes	No

LOCATION		QTY				
Head drip	Standard	Vented				
Add-on (Top)	20mm	2.5mm coupler				
Add-on (Left)	20mm	20mm	2.5mm coupler			
EXTERNAL VIEW						
Add-on (Bottom)	20mm		2.5mm coupler			
Cill type	85mm	150mm	165mm	185mm	225mm	None
Drainage	Concealed		Face	None		

LOCATION		QTY				
Head drip	Standard	Vented				
Add-on (Top)	20mm	2.5mm coupler				
Add-on (Left)	20mm	20mm	2.5mm coupler			
EXTERNAL VIEW						
Add-on (Bottom)	20mm		2.5mm coupler			
Cill type	85mm	150mm	165mm	185mm	225mm	None
Drainage	Concealed		Face	None		

LOCATION		QTY				
Head drip	Standard	Vented				
Add-on (Top)	20mm	2.5mm coupler				
Add-on (Left)	20mm	20mm	2.5mm coupler			
EXTERNAL VIEW						
Add-on (Bottom)	20mm		2.5mm coupler			
Cill type	85mm	150mm	165mm	185mm	225mm	None
Drainage	Concealed		Face	None		

Width	(including add-on)			
Height	(including cill)			
Mullion centre	(if not 600mm)			
Transom drop	(if not 400mm)			
Ventilator type	None	2000 EA	4000 EA	5000 EA
Ventilator position	Frame		Sash	
Handle type	Standard	Monkey Tail	Pear drop	
Handle colour				
Locking system	Shootbolt			
Sash stay bar	Yes	No		
Hinge protectors	Yes	No		
Friction stays	Standard	Restricted	Egress	Egress Easy Clean
Glass type	Annealed		Toughened	Laminated
Glass appearance	Clear	Patterned:		
Glass decoration				
Spacer bar colour				

Width	(including add-on)			
Height	(including cill)			
Mullion centre	(if not 600mm)			
Transom drop	(if not 400mm)			
Ventilator type	None	2000 EA	4000 EA	5000 EA
Ventilator position	Frame		Sash	
Handle type	Standard	Monkey Tail	Pear drop	
Handle colour				
Locking system	Shootbolt			
Sash stay bar	Yes	No		
Hinge protectors	Yes	No		
Friction stays	Standard	Restricted	Egress	Egress Easy Clean
Glass type	Annealed		Toughened	Laminated
Glass appearance	Clear	Patterned:		
Glass decoration				
Spacer bar colour				

Width	(including add-on)			
Height	(including cill)			
Mullion centre	(if not 600mm)			
Transom drop	(if not 400mm)			
Ventilator type	None	2000 EA	4000 EA	5000 EA
Ventilator position	Frame		Sash	
Handle type	Standard	Monkey Tail	Pear drop	
Handle colour				
Locking system	Shootbolt			
Sash stay bar	Yes	No		
Hinge protectors	Yes	No		
Friction stays	Standard	Restricted	Egress	Egress Easy Clean
Glass type	Annealed		Toughened	Laminated
Glass appearance	Clear	Patterned:		
Glass decoration				
Spacer bar colour				

Notes / Special requirements

Notes / Special requirements

Notes / Special requirements